

General Specifications

Dimensions

Ground Clearance	16 in (41 cm)
------------------	---------------

Height - Top of Cab	7 ft (2 m)
---------------------	------------

Length - without Bucket	10 ft (3 m)
-------------------------	-------------

Width Over Tracks	6 ft (2 m)
-------------------	------------

Engine

Aspiration	Turbocharged
------------	--------------

Displacement	244 cu in (3,998 cu cm)
--------------	-------------------------

Engine Model	3054T
--------------	-------

Gross Power	105 hp (78 kw)
-------------	----------------

Peak Torque	284 lbs ft (385 nm)
-------------	---------------------

Power Measured @	2400 rpm
------------------	----------

Hydraulic System

Pump Flow	19 gpm (72 lpm)
-----------	-----------------

Relief Valve Pressure	2950 psi
-----------------------	----------

Loader

Breakout Force	5,900 lbs (2,676 kg)
----------------	----------------------

Operating Load	2,065 lbs (937 kg)
----------------	--------------------

Operating Specifications

Alternator Supplied Amperage	65 amps
------------------------------	---------

Cooling System Fluid Capacity	10 gal (36 l)
-------------------------------	---------------

Engine Oil Capacity	2 gal (8 l)
---------------------	-------------

Fuel Capacity	25 gal (95 l)
---------------	---------------

Hydraulic System Fluid Capacity	28 gal (106 l)
---------------------------------	----------------

Max Speed - high range	6 mph (10 kph)
------------------------	----------------

Operating Voltage	12 volts
-------------------	----------

Operating Weight	8,640 lbs (3,919 kg)
------------------	----------------------

Undercarriage

Ground Contact Area	2,826 cu in (46,310 cu cm)
---------------------	----------------------------

Ground Pressure	3 psi
-----------------	-------

Length of Track on Ground	7 ft (2 m)
---------------------------	------------

Number of Track Rollers per Side	12
----------------------------------	----

Width of Track	18 in (46 cm)
----------------	---------------