

# T110 Compact Track Loader

Year(s) of Production: 2009

When you visit this website, cookies are placed on your device. These cookies allow us among other things to offer you the best possible user experience, to show you relevant commercial messages and to collect statistical information regarding this website. By clicking "I AGREE", you indicate that you have read all information concerning our use of cookies and the processing of personal data and that you consent unambiguously to the placement of cookies as set out in our [Cookie policy](#).

[Shop For Parts](#)

[Service Schedules](#)

[Cookie Settings](#)

[Reject All](#)

[I Agree](#)

[Order Manuals](#)

[Operator Training](#)

[Used Inventory](#)

## T110 Specifications

T110 Key Specifications	
Rated Operating Capacity (ISO)	1,100 lb
Operating Weight	5202 lb
Ground Pressure (Rubber)	4.6 psi
Auxiliary Std Flow	12.5 gal/min
Joystick Control	Optional

Engine	
Emissions Tier (EPA)	Interim Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	41.8 hp
Turbocharged Engine	no

Performance	
Rated Operating Capacity (ISO)	1,100 lb
Operating Capacity (50% of Tip)	1595 lb
Tipping Load	3190 lb
Operating Weight	5202 lb



Travel Speed	5.2 mph
Travel Speed (2-speed option)	8.4 mph
Ground Pressure (Rubber)	4.6 psi

### Capacities

Fuel Tank
-----------

When you visit this website, cookies are placed on your device. These cookies allow us among other things to offer you the best possible user experience, to show you relevant commercial messages and to collect statistical information regarding this website. By clicking "I AGREE", you indicate that you have read all information concerning our use of cookies and the processing of personal data and that you consent unambiguously to the placement of cookies as set out in our [Cookie policy](#).

### Hydraulic System

System Relief @ Quick Couplers	3,000 psi
Auxiliary Std Flow	12.5 gal/min

### Dimension

Length	89.1 in
Length without Attachment	89.1 in
Length with Standard Bucket	117 in
Width	47.2 in
Width (with bucket)	50 in
Height	74.1 in
Height with Operator Cab	74.1 in
Height to Bucket Hinge Pin	103.7 in
Reach @ Maximum Height	22.8 in
Turning Radius	72.9 in
Length of track on ground	51.1 in
Track Width	9.8 in

### Features

Joystick Control	Optional
Air Conditioning	Not Applicable
Backup Alarm	Standard
BICS System (Interlock)	Standard
Cab Heater	Optional
Operating Lights	Standard
Suspension Seat	Standard
Two Speed Travel	Optional



Deluxe Instrumentation	Optional
Engine Shutdown	Standard
Hydraulic Bucket Positioning	Optional
High Flow Option	<div>When you visit this website, cookies are placed on your device. These cookies allow us among other things to offer you the best possible user experience, to show you relevant commercial messages and to collect statistical information regarding this website. By clicking "I AGREE", you indicate that you have read all information concerning our use of cookies and the processing of personal data and that you consent unambiguously to the placement of cookies as set out in our <a href="#">Cookie policy</a>.</div> <div><a href="#">Cookie Settings</a><div>Reject AllI Agree</div></div>
Auxiliary Hydraulics	
Bob-Tach Attachment Sys	
Power Bob-Tach	
ACS (Switchable Controls)	Not Applicable
Ride Control	Not Applicable
Horn	Standard
Power Qtach	Not Applicable

# Search for Parts

Q

Search by Serial Number, Part Number or Keyword

Search



**WARNING:** This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.