



Search By Category, Manufacturer, Location, Stock # or Keywords

410L BACKHOE

HOME / 410L BACKHOE

410L BACKHOE

- Net Peak Power: 87 kW (116 hp) at 1,900 rpm
- Max Standard Dipperstick Digging Depth: 4.85 m (15 ft. 11 in.)
- Operating Weight: 8,068 kg (17,786 lb.)

GET A QUOTE		
VALUE YOUR TRADE		
WRITE A REVIEW		



FEATURES

ENGINE

POWERSHIFT™ TRANSMISSION

MECHANICAL-FRONT-WHEEL DRIVE

CAB AND CONTROLS

LIFT CAPACITY

EASY MAINTENANCE

SECURITY

SPECIFICATIONS

Dump Height - General Purpose, mm

(ft/in)

DRIVELINE

DRIVELINE	
Engine Manufacturer	John Deere
Engine Model	PowerTech EWL 4045HL050
Displacement, ltr (Inches ³)	4.5 (276)
Rated Speed, rpm	1900
Engine Output - Net, kW (hp)	87 (116)
Transmission Type	Powershift
Service Brake Type	Wet Multi Disc
Service Brake Actuation	Hydraulic w/Power Assist
DIMENSIONS	
Max length with std. Stick, mm (ft/in)	7430 (24 ft 5 in)
Max length with ext. Stick, mm (ft/in)	7340 (24 ft 5 in)
Height over std Stick, mm (ft/in)	3910 (12 ft 10 in)
Height over ext Stick, mm (ft/in)	3910 (12 ft 10 in)
Maximum Width, mm (ft/in)	2350 (7 ft 9 in)
Width over tires, mm (ft/in)	2340 (7 ft 8 in)
Wheelbase - 4WD, mm (ft/in)	2190 (7 ft 2 in)
Ground Clearance, mm (inches)	334 (13)
Width - General Purpose Bucket, mm (ft/in)	2346 (7 ft 8 in) - HD
Bucket Rotation - Position 1, Degrees	190
Bucket Pin Height - General Purpose, mm (ft/in)	3470 (11 ft 4 in)
Duran Haiaht Canaval Duranga	2700 (0 € 10 :-) UD

2700 (8 ft 10 in) - HD

Dump Reach - General Purpose, mm (inches)	730 (28.7) - HD
Digging Depth - General Purpose, mm (inches)	135 (5.3) - HD
CAPACITIES	
Fuel Tank, ltr (gallons (US))	128.7 (34)
Hydraulic Tank, ltr (gallons (US))	45 (11.9)
Rear Axle, ltr (gallons (US))	18 (4.75)
4WD Front Axle, ltr (gallons (US))	6.5 (1.725)
Capacity Heaped - Bucket 1, m³ (ft³)	0.21 (7.5)
Bucket Capacity - Standard General Purpose, m³ (yd³)	1 (1.31)
Battery Voltage, V	12
Bucket Tearout - Non-Extending Dipper, kN (lbf)	77.2 (17350) - Lift Mode
Stick tearout, kN (lbf)	48.6 (10932) - Lift Mode
Boom Lift - Maximum Reach - Non- Extending Dipper, kg (lbs)	2490 (5489) - Lift Mode
Bucket Breakout - General Purpose, kN (lbf)	47.3 (10645)
Lift To Full Height - General Purpose Bucket, kg (lbs)	3271 (7211)
Pump	Axial Piston Pump
Pump Flow, lt/min (gallons (US) / min)	159 (42)
WEIGHTS	
Operating Weight, kg (lbs)	8178 (18028)
Weight - 4WD, GP, std Stick, kg (lbs)	8178 (18028)

The 410L Backhoe; available at all the following C & B Locations:

TURF

UTILITY VEHICLES

COMPACT CONSTRUCTION

BUILD YOUR OWN

DEALER TRANSFER REQUEST FORM

USED EQUIPMENT

VIEW ALL IN-STOCK EQUIPMENT

ONLINE AUCTION

HOT DEALS

EXPORT/WHOLESALE

DEALER TRANSFER REQUEST FORM

PARTS

ORDER PARTS ONLINE

ALL MAKES PARTS

C & B PARTS BARGAIN BIN

PARTS DROP BOXES

SEARCH FOR PARTS

AFTER-HOURS SUPPORT

PARTS SPECIALS

SIGNATURE FUEL SYSTEMS

C & B RETURN/RESTOCK POLICY

DEALER TRANSFER REQUEST

SERVICE

SERVICE SPECIALS

DO IT YOURSELF REPAIRS

OPERATING MANUALS

EZCARE PROTECTION PLAN

C & B CENTRAL

POWERGARD™ PLANS

AFTER-HOURS SUPPORT

PRECISION AG

BASIC & ADVANCED DATA SERVICES

C & B AGRONOMIC PLOT

TECHNOLOGY THURSDAY

VALUE ADDED SERVICES

SUPPORT CENTER

CUSTOMER DIGITAL TOOLS

ABOUT US

HISTORY

CAREERS

PROMOTIONS

C & B COMMUNITY IMPACT

C & B BLOG

EVENTS

C & B LOCATIONS

ROAD TO SUCCESS

CONTACT US

. IND A DEALER

Enter Zip	
CET LIBRATES	
GET UPDATES	
Email	
Policy Center Privacy Policy Terms of Use Accessibility Statement	
	⊚ f □ in
	Copyright © 2025 All Rights Reserved by C & B Operations, LLC.