



Examples: 'Bobcat Skid Steers', 'Komatsu Dealers', 'Groff Tractor', 'Cat 316', 'Toda

Search

[CATEGORIES](#) → [CRAWLER DOZERS](#) → [CATERPILLAR D4C HST XL III](#)

Caterpillar D4C HST XL III Crawler Dozer

CATEGORY: CRAWLER DOZERS →

MANUFACTURER: CATERPILLAR →

MODEL: D4C HST XL III →

Introducing the Caterpillar D4C HST XL III Crawler Dozer, a powerful and efficient machine designed for heavy-duty earthmoving tasks. This rugged dozer boasts an engine displacement of 305 cubic inches and a gross power of 88 horsepower, ensuring optimal performance on the job site. With features like a hydraulic system pump flow capacity of 17.6 gallons per minute and a standard blade width of 9 feet, this dozer is built to tackle tough terrain with ease. The D4C HST XL III offers operators a reliable and versatile solution for all their earthmoving needs.

[See all Caterpillar D4C HST XL IIIs for sale](#)

General Specifications

Dimensions

Ground Clearance	1 ft (0 m)
Height - Top of Cab	9 ft (3 m)
Length of Track on Ground	7 ft (2 m)



Length w/o Blade	10 ft (3 m)
Width Over Tracks	7 ft (2 m)

Engine

Aspiration	Natural
Displacement	305 cu in (4,998 cu cm)
Engine Model	Cat 3046
Gross Power	88 hp (66 kw)
Net Power	81 hp (60 kw)
Number of Cylinders	6
Power Measured @	2400 rpm

Hydraulic System

Pump Flow Capacity	18 gpm (67 lpm)
Pump type	Gear
Relief Valve Pressure	2500 psi

Operating Specifications

Alternator Supplied Amperage	55 amps
Cooling System Fluid Capacity	6 gal (21 l)
Engine Oil Capacity	4 gal (13 l)

Fuel Capacity	42 gal (157 l)
Hydraulic Fluid Capacity	15 gal (57 l)
Operating Voltage	12 volts
Operating Weight	16,574 lbs (7,518 kg)

Standard Blade

Blade Angle (both directions)	25 degrees
Capacity	2 cu yd (2 cu m)
Height	37 in (93 cm)
Width	9 ft (3 m)

Transmission

Max Speed - Forward	6 mph (9 kph)
Max Speed - Reverse	6 mph (9 kph)
Number of Forward Gears	3
Number of Reverse Gears	3
Transmission Type	Hydrostatic

Undercarriage

Ground Contact Area	3,131 cu in (51,308 cu cm)
Ground Pressure	5.3 psi

Number of Track Rollers per Side

7

Standard Shoe Size

18 in (46 cm)

Track Gauge5 ft (2 m)



Our Main Office

Construction Equipment Guide

470 Maryland Drive

Fort Washington, PA 19034

800-523-2200

About Us

Construction Equipment Guide covers the nation with its four regional newspapers, offering construction and industry news and information along with new and used construction equipment for sale from dealers in your area. Now we extend those services and information to the internet. Making it as easy as possible to find the news and equipment that you need and want.

Contents Copyrighted 2025, by Construction Equipment Guide, which is a Registered Trademark, registered in the U.S. Patent Office. Registration number 0957323. All rights reserved, nothing may be reprinted or reproduced (including framing) in whole or part without written permission from the publisher. All editorial material, photographs, drawings, letters, and other material will be treated as unconditionally assigned for publication and copyright purposes and are subject to

[Read our privacy policy here.](#)

Mastodon

33.51940 \\ 36.28880 \\ Damascus \\ DI \\ SY \\ Unknown