

 SHARE

Compact Track Loaders / T595 Compact Track Loader

Specification & Options

■ Standard
 ✓ Optional
 N/A Not Applicable

 Units **US**

Bobcat T595

Configuration

Standard

Roller Suspension Option

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (SAE)	2,200 lb
Operating Capacity (50% of Tip)	3142 lb
Tipping Load	6285 lb
Operating Weight	8055 lb
Travel Speed	7.1 mph
Travel Speed (2-speed option)	10.4 mph
Ground Pressure (Rubber)	5.1 psi

Capacities

Fuel Tank	36.5 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	17.1 gal/min
Auxiliary High Flow	26.7 gal/min

Dimension

Length	133 in
Length without Attachment	104.6 in
Length with Standard Bucket	133 in
Width	67.1 in
Width (with bucket)	68 in
Height	77.8 in
Height with Operator Cab	77.8 in
Height to Bucket Hinge Pin	119 in
Reach @ Maximum Height	34.9 in
Turning Radius	80 in
Length of track on ground	54.1 in
Track Width	12.6 in
Track Width - Optional	15.8 in

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.