

 SHARE

Compact Track Loaders / T630 Compact Track Loader

Specifications & Options

■ Standard
 ☑ Optional
 N/A Not Applicable

Units US

Bobcat T630

Configuration

Standard

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (SAE)	2,100 lb
Operating Capacity (50% of Tip)	3000 lb
Tipping Load	6000 lb
Operating Weight	8555 lb
Travel Speed	6.2 mph
Travel Speed (2-speed option)	10 mph
Ground Pressure (Rubber)	5.3 psi

Capacities

Fuel Tank	43.9 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/min
Auxiliary High Flow	30.5 gal/min

Dimension

Length	108.4 in
Length without Attachment	108.4 in
Length with Standard Bucket	136.8 in
Width	72.9 in
Width (with bucket)	74 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	121 in
Reach @ Maximum Height	24.1 in
Turning Radius	88.1 in
Length of track on ground	58.5 in
Track Width	12.6 in
Track Width - Optional	17.7 in

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.