



Examples: 'Bobcat Skid Steers', 'Komatsu Dealers', 'Groff Tractor', 'Cat 316', 'Toda

Search

[CATEGORIES](#) → [CRAWLER DOZERS](#) → [KOMATSU D20A-3](#)

Komatsu D20A-3 Crawler Dozer

CATEGORY: [CRAWLER DOZERS](#) →**MANUFACTURER:** [KOMATSU](#) →**MODEL:** [D20A-3](#) →

The Komatsu D20A-3 Crawler Dozer is a versatile and powerful machine designed for a variety of earthmoving and construction applications. With its compact dimensions and impressive operating weight of 7341.4 lbs, this dozer is equipped to handle even the toughest tasks with ease. Powered by a 35 hp 4-cylinder engine, the D20A-3 offers reliable performance and efficiency. Its standard blade capacity of 1 cu yd, along with a blade width of 7.6 ft and height of 22.3 in, ensures efficient material movement and leveling. The dozer's transmission type, DD, provides smooth and precise control, while its undercarriage features 37 shoes per side and 5 track rollers per side for stability and traction. From its top of cab height of 6.9 ft to its ground clearance of 1.1 ft, the Komatsu D20A-3 is a top choice for operators seeking a rugged and dependable dozer for their worksite.

[See all Komatsu D20A-3s for sale](#)

General Specifications

Dimensions

Ground Clearance

1 ft (0 m)



Length of Track on Ground	6 ft (2 m)
----------------------------------	------------

Length w/ Blade	11 ft (3 m)
------------------------	-------------

Length w/o Blade	8 ft (2 m)
-------------------------	------------

Width Over Tracks	5 ft (2 m)
--------------------------	------------

Engine

Displacement	159 cu in (2,601 cu cm)
---------------------	-------------------------

Engine Model	4D95-1A
---------------------	---------

Gross Power	35 hp (26 kw)
--------------------	---------------

Number of Cylinders	4
----------------------------	---

Power Measured @	2450 rpm
-------------------------	----------

Operating Specifications

Cooling System Fluid Capacity	4 gal (14 l)
--------------------------------------	--------------

Fuel Capacity	16 gal (60 l)
----------------------	---------------

Operating Weight	7,341 lbs (3,330 kg)
-------------------------	----------------------

Standard Blade

Capacity	1 cu yd (1 cu m)
-----------------	------------------

Height	22 in (57 cm)
---------------	---------------

Width	8 ft (2 m)
--------------	------------

Transmission

Max Speed - Forward 5 mph (7 kph)

Max Speed - Reverse 4 mph (7 kph)

Number of Forward Gears 3

Number of Reverse Gears 2

Transmission Type DD

Undercarriage

Ground Pressure 4 psi

Number of Shoes per Side 37

Number of Track Rollers per Side 5

Standard Shoe Size 12 in (30 cm)

Track Gauge 4 ft (1 m)

Track Pitch 5 in (14 cm)



Our Main Office

Construction Equipment Guide
470 Maryland Drive
Fort Washington, PA 19034
800-523-2200

About Us

Construction Equipment Guide covers the nation with its four regional newspapers, offering construction and industry news and information along with new and used construction equipment for sale from dealers in your area. Now we extend those services and information to the internet. Making it as easy as possible to find the news and equipment that you need and want.

Contents Copyrighted 2025, by Construction Equipment Guide, which is a Registered Trademark, registered in the U.S. Patent Office. Registration number 0957323. All rights reserved, nothing may be reprinted or reproduced (including framing) in whole or part without written permission from the publisher. All editorial material, photographs, drawings, letters, and other material will be treated as unconditionally assigned for publication and copyright purposes and are subject to Construction Equipment Guide's unrestricted right to edit and comment editorially. Contributor articles do not necessarily reflect the policy or opinions of this publication.

[Read our privacy policy here.](#)

Mastodon