

[Home](#)

Komatsu D37EX-22 Crawler Tractor



Units

Imperial

Metric

Dimensions

Dimensions

A	Length W/ Blade	13.7 ft in
B	Width Over Tracks	6.27 ft in
C	Height To Top Of Cab	9.06 ft in
D	Length Of Track On Ground	7.17 ft in

E	<b>Ground Clearance</b>	1.04 ft in
Undercarriage		
G	<b>Track Gauge</b>	4.96 ft in
H	<b>Standard Shoe Size</b>	15.75 in
	<b>Number Of Track Rollers(Each Side)</b>	6
	<b>Ground Contact Area</b>	2.78 in <sup>2</sup>
	<b>Shoe Width (Standard)</b>	15.75 in
	<b>Suspension</b>	Rigid type
	<b>Track Rollerframe</b>	Monochoque,large Section
	<b>Type Of Shoes(Standard)</b>	Single grouser
	<b>Rollers And Idlers</b>	Lubricated track rollers
	<b>Ground Pressure</b>	6.68 psi
	<b>Grouser Height</b>	1.86 in
	<b>Length Of Track Ground</b>	86.03 in
	<b>Number Of Shoes (Each Side)</b>	41

---

## Specifications

Steering System		
	<b>Minimum Turning Radius</b>	6.6 ft in
Engine		
	<b>Hydraulic Fan At Maximum Speed</b>	79.2 hp
	<b>Lubrication Method</b>	Gear pump ,Force Lubrication
	<b>Filter</b>	Full Flow
	<b>Epa</b>	Tier -3 Emission certified
	<b>Number Of Cylinders</b>	4
	<b>Piston Displacement</b>	199 cu in
	<b>Engine Make</b>	2238
	<b>Engine Model</b>	SAA4D95LE-5

<b>Engine Type</b>	4-Cycle,water-Cooled,Direct injection
<b>Gross Power</b>	80 hp
<b>Governor</b>	All-speed Electronic
<b>Net Power</b>	78 hp
<b>Power Measured @</b>	2200 rpm
<b>Displacement</b>	199 cu in
<b>Aspiration</b>	Turbocharged, air-to-air aftercooled
<b>Bore</b>	3.8 in
<b>Stroke</b>	4.6 in
<b>Horse Power: Sae J1995</b>	91.2 hp
<b>Horse Power: Iso 9249 / Sae J1349</b>	88.6 hp
<b>Fan Drive Type</b>	Hydraulic (Reversible for cleaning)
Capacities	
<b>Fuel Tank - Diesel</b>	51.6 gal
<b>Hydraulic Tank</b>	15.9 gal
<b>Final Drive</b>	1 gal
<b>Engine Oil</b>	3 gal
<b>Coolant</b>	4.8 gal
Operational	
<b>Blade Capacity</b>	2.4 yd3
<b>Blade Type</b>	PAT
<b>Blade Length</b>	106.7 in
<b>Blade Height</b>	33.9 in
<b>Blade Cut Depth</b>	15.8 in
<b>Ripper Type</b>	Fixed
<b>Ripper Depth</b>	13.4 in
Transmission	
<b>Transmission Type</b>	dual-path, hydrostatic

<b>Number Of Forward Gears</b>	3
<b>Number Of Reverse Gears</b>	3
<b>Max Speed - Forward</b>	5.3 mph
<b>Max Speed - Reverse</b>	5.3 mph
Weights	
<b>Tractor Weight - Rops Canopy</b>	14793.1 lb
<b>Tractor Weight - Rops Cab</b>	15697 lb
<b>Operating Weight - Rops Canopy</b>	17394.5 lb
<b>Operating Weight - Rops Cab</b>	18298.4 lb
Hydraulic System	
<b>Blade Lift(No.Of.Cylinders)</b>	2
<b>Blade-Tilit(No.Of.Cylinders)</b>	1
<b>Blade Angle(No.Of.Cylinders)</b>	2
<b>Blade Lift(Bore)</b>	0.3 ft in
<b>Blade-Tilit(Bore)</b>	0.3 ft in
<b>Blade Angle(Bore)</b>	0.3 ft in
<b>Hydraulic Oil Capacity(Power Angle Tilt Dozer)</b>	15.9 gal
<b>Relief Valve Pressure</b>	3983 psi
<b>Pump Flow Capacity</b>	26.2 gal/min
Standard Blade	
<b>Width</b>	8.4 ft in
<b>Height</b>	33.1 in
<b>Capacity</b>	2.2 yd3
<b>Blade Angle (Both Directions)</b>	25 degrees
<b>Cutting Depth</b>	15.4 in

---

## Compare similar models



[Komatsu D39EX22](#)

Ground Pressure	6 psi
Net Power	78 hp
<input type="checkbox"/> <a href="#">Caterpillar D3B</a>	
Ground Pressure	--
Net Power	65 hp
<input type="checkbox"/> <a href="#">Komatsu D31EX-22</a>	
Ground Pressure	6.7 psi
Net Power	78 hp
Compare	

Find {{brand}} {{model}} {{category}} for Sale

[See {{brand}} {{category}} for sale rbauction.com](#)  
[See {{brand}} {{category}} for sale ironplanet.com](#)  
[See {{brand}} {{category}} for sale mascus.com](#)

Need help? Contact Us

English

Company

Popular Searches

Looking for equipment or trucks?

Ritchie Bros. sells more new and used industrial equipment and trucks than any other company in the world.

Equipment for sale on rbauction.com

Equipment for sale on ironplanet.com

Equipment for sale on mascus.com

Sell your equipment