



Examples: 'Bobcat Skid Steers', 'Komatsu Dealers', 'Groff Tractor', 'Cat 316', 'Today's

Search

[CATEGORIES](#) → [COMPACT TRACK LOADERS](#) → [CATERPILLAR 267](#)

Caterpillar 267 Compact Track Loader

CATEGORY: COMPACT TRACK LOADERS →

MANUFACTURER: CATERPILLAR →

MODEL: 267 →

Introducing the Caterpillar 267 Compact Track Loader, a powerful and versatile machine designed to handle tough jobs with ease. With a gross power of 63 horsepower and a loader operating load of 2900 pounds, this compact track loader offers impressive performance capabilities. Its compact design, with dimensions including a reach of 2.3 feet at max lift and dump, makes it ideal for navigating tight spaces. The Caterpillar 267 also boasts an operating weight of 9154 pounds and a tipping load of 5800 pounds, making it a reliable choice for a range of applications.

[See all Caterpillar 267s for sale](#)

General Specifications

Dimensions

Clearance at Max Lift and Dump

8 ft (2 m)

Ground Clearance

14 in (35 cm)

Height - Top of Cab

7 ft (2 m)

Length - with Bucket	12 ft (4 m)
Length - without Bucket	10 ft (3 m)
Reach at Max Lift and Dump	2 ft (1 m)
Turning Radius from Center - inc bucket	99 in (251 cm)
Width Over Tracks	6 ft (2 m)

Engine

Aspiration	Natural
Bore	4 in (10 cm)
Displacement	183 cu in (2,999 cu cm)
Engine Model	Cat 3034 naturally aspirated
Gross Power	63 hp (47 kw)
Net Power	59 hp (44 kw)
Number of Cylinders	4
Power Measured @	2600 rpm
Stroke	4 in (10 cm)

Hydraulic System

Pump Flow	22 gpm (82 lpm)
------------------	-----------------

Loader

Bucket Capacity	1 cu yd (0 cu m)
Operating Load	2,900 lbs (1,315 kg)
Tipping Angle	6583 degrees

Operating Specifications

Breakout Force - Lift Cylinder	4,339 lbs (1,968 kg)
Breakout Force - Tilt Cylinder	5,259 lbs (2,385 kg)
Fuel Capacity	22 gal (82 l)
Ground Contact Area	2,898 cu in (47,490 cu cm)
Ground Pressure	3.1 psi
Hydraulic System Fluid Capacity	14 gal (52 l)
Max Speed - high range	6 mph (10 kph)
Operating Weight	9,154 lbs (4,152 kg)
Rated Operating Capacities - 35% Tipping Load	2,030 lbs (921 kg)
Rated Operating Capacities - 50% Tipping Load	2,900 lbs (1,315 kg)
Tipping Load	5,800 lbs (2,631 kg)

Power Train

Travel Speed Forward	6 mph (10 kph)
Travel Speed Reverse	6 mph (10 kph)

Service Refill Capacities

Cooling System	3 gal (10 l)
----------------	--------------

Engine Crankcase	2 gal (7 l)
------------------	-------------

Fuel Tank	23 gal (86 l)
-----------	---------------

Hydraulic System	14 gal (52 l)
------------------	---------------

Hydraulic Tank	9 gal (35 l)
----------------	--------------

Undercarriage

Length of Track on Ground	7 ft (2 m)
---------------------------	------------

Width of Track	18 in (45 cm)
----------------	---------------

Weights

Operating Weight	9,088 lbs (4,122 kg)
------------------	----------------------

