



Examples: 'Bobcat Skid Steers', 'Komatsu Dealers', 'Groff Tractor', 'Cat 316', 'Today's

Search

CATEGORIES → BACKHOE LOADERS → TEREX 880SX

Terex 880SX Backhoe Loader

CATEGORY: BACKHOE LOADERS →

MANUFACTURER: TEREX →

MODEL: 880SX →

See all Terex 880SXs for sale

General Specifications

Backhoe

Bucket Dig Force	11,596 lbs (5,260 kg)
Bucket Dig Force - Extended	11,596 lbs (5,260 kg)
Dig Depth	15 ft (4 m)
Dig Depth - Extended	19 ft (6 m)
Load Height - Extended	15 ft (5 m)
Reach at Load Height - Extended	10 ft (3 m)
Reach From Swivel	19 ft (6 m)

Reach From Swivel - Extended

23 ft (7 m)

Dimensions

Ground Clearance

2 ft (0 m)

Height to Top of Suspended Cab

9 ft (3 m)

Transport Length

24 ft (7 m)

Transport Width

8 ft (2 m)

Wheelbase

7 ft (2 m)

Engine

Displacement

269 cu in (4,408 cu cm)

Engine Model

1104C-44T

Gross Power

100 hp (75 kw)

Net Max Torque

305 lbs ft (414 nm)

Net Power

94 hp (70 kw)

Power Measured @

2200 rpm

Torque Measured @

1400 rpm

Hydraulic System

Pump Flow Capacity

42 gpm (160 lpm)

Pump Type

twin gear

Relief Valve Pressure	3250 psi
------------------------------	----------

Loader

Bucket Breakout Force	12,291 lbs (5,575 kg)
------------------------------	-----------------------

Bucket Capacity	1 cu yd (1 cu m)
------------------------	------------------

Bucket Width	91 in (231 cm)
---------------------	----------------

Clearance at Max Dump Height	9 ft (3 m)
-------------------------------------	------------

Dig Depth	5 in (12 cm)
------------------	--------------

Reach at Max Dump Height	2 ft (1 m)
---------------------------------	------------

Operating Specifications

Alternator Supplied Amperage	75 amps
-------------------------------------	---------

Cooling System Fluid Capacity	4 gal (16 l)
--------------------------------------	--------------

Front Axle Fluid Capacity	3 gal (13 l)
----------------------------------	--------------

Fuel Capacity	34 gal (130 l)
----------------------	----------------

Hydraulic System Fluid Capacity	38 gal (143 l)
--	----------------

Max Weight	16,214 lbs (7,355 kg)
-------------------	-----------------------

Oil System Fluid Capacity	2 gal (9 l)
----------------------------------	-------------

Operating Voltage	12 volts
--------------------------	----------

Rear Axle Fluid Capacity	5 gal (18 l)
---------------------------------	--------------

Tire Size Front - 2wd / 4wd	16/70x20
------------------------------------	----------

Transmission Fluid Capacity	4 gal (15 l)
Turning Radius	13 ft (4 m)

Tires	
Rear Tires Size	18.4x26

Transmission	
Max Speed	25 mph (40 kph)
Max Speed - Reverse	26 mph (42 kph)
Number of Forward Gears	4
Number of Reverse Gears	4
Transmission Type	Syncrho shuttle gearbox



Our Main Office