



Search

[CATEGORIES](#) → [COMPACT TRACK LOADERS](#) → [GEHL CTL85](#)

# Gehl CTL85 Compact Track Loader

**CATEGORY:** [COMPACT TRACK LOADERS](#) →**MANUFACTURER:** [GEHL](#) →**MODEL:** [CTL85](#) →[See all Gehl CTL85s for sale](#)

## General Specifications

---

### Dimensions

---

<b>Clearance at Max Lift and Dump</b>	8 ft (2 m)
<b>Ground Clearance</b>	14 in (35 cm)
<b>Height - Top of Cab</b>	7 ft (2 m)
<b>Length - with Bucket</b>	13 ft (4 m)
<b>Length - without Bucket</b>	10 ft (3 m)
<b>Reach at Max Lift and Dump</b>	4 ft (1 m)
<b>Turning Radius from Center - inc bucket</b>	106 in (269 cm)

---

<b>Turning Radius from Center - machine rear</b>	72 in (182 cm)
--	----------------

---

<b>Width Over Tracks</b>	6 ft (2 m)
--------------------------	------------

---

## Engine

---

<b>Aspiration</b>	Turbocharged
-------------------	--------------

---

<b>Displacement</b>	230 cu in (3,769 cu cm)
---------------------	-------------------------

---

<b>Engine Model</b>	V3800DI-T
---------------------	-----------

---

<b>Gross Power</b>	92 hp (69 kw)
--------------------	---------------

---

<b>Number of Cylinders</b>	4
----------------------------	---

---

<b>Peak Torque</b>	240 lbs ft (325 nm)
--------------------	---------------------

---

<b>Power Measured @</b>	2200 rpm
-------------------------	----------

---

<b>Torque Measured @</b>	1600 rpm
--------------------------	----------

---

## Hydraulic System

---

<b>Pump Flow</b>	24 gpm (89 lpm)
------------------	-----------------

---

<b>Relief Valve Pressure</b>	2988 psi
------------------------------	----------

---

## Loader

---

<b>Bucket Capacity</b>	1 cu yd (1 cu m)
------------------------	------------------

---

<b>Operating Load</b>	3,527 lbs (1,600 kg)
-----------------------	----------------------

---

<b>Tipping Angle</b>	7054.8 degrees
----------------------	----------------

---

## Operating Specifications

---

<b>Alternator Supplied Amperage</b>	80 amps
<b>Cooling System Fluid Capacity</b>	4 gal (17 l)
<b>Engine Oil Capacity</b>	4 gal (13 l)
<b>Fuel Capacity</b>	29 gal (108 l)
<b>Hydraulic System Fluid Capacity</b>	16 gal (60 l)
<b>Max Speed - high range</b>	8 mph (12 kph)
<b>Max Speed - low range</b>	5 mph (8 kph)
<b>Operating Voltage</b>	12 volts
<b>Operating Weight</b>	11,222 lbs (5,090 kg)

## Undercarriage

---

<b>Ground Pressure</b>	4.5 psi
<b>Length of Track on Ground</b>	5 ft (2 m)
<b>Number of Track Rollers per Side</b>	5
<b>Width of Track</b>	18 in (46 cm)