



Examples: 'Bobcat Skid Steers', 'Komatsu Dealers', 'Groff Tractor', 'Cat 316', 'Today's

Search

[CATEGORIES](#) → [COMPACT TRACK LOADERS](#) → [ASV PT-80](#)

# ASV PT-80 Compact Track Loader

**CATEGORY:** [COMPACT TRACK LOADERS](#) →

**MANUFACTURER:** [ASV](#) →

**MODEL:** [PT-80](#) →

[See all ASV PT-80s for sale](#)

## General Specifications

---

### Dimensions

---

<b>Clearance at Max Lift and Dump</b>	8 ft (2 m)
<b>Ground Clearance</b>	15 in (38 cm)
<b>Height - Top of Cab</b>	7 ft (2 m)
<b>Length - with Bucket</b>	12 ft (4 m)
<b>Length - without Bucket</b>	9 ft (3 m)
<b>Reach at Max Lift and Dump</b>	2 ft (1 m)
<b>Width Over Tracks</b>	6 ft (2 m)

## Engine

---

<b>Aspiration</b>	Turbocharged
<b>Displacement</b>	202 cu in (3,310 cu cm)
<b>Engine Model</b>	804C-33T
<b>Gross Power</b>	81 hp (60 kw)
<b>Peak Torque</b>	186 lbs ft (252 nm)

## Hydraulic System

---

<b>Pump Flow</b>	30 gpm (114 lpm)
<b>Relief Valve Pressure</b>	3000 psi

## Loader

---

<b>Operating Load</b>	3,100 lbs (1,406 kg)
<b>Tipping Angle</b>	6200 degrees

## Operating Specifications

---

<b>Alternator Supplied Amperage</b>	90 amps
<b>Cooling System Fluid Capacity</b>	3 gal (11 l)
<b>Engine Oil Capacity</b>	9 gal (34 l)
<b>Fuel Capacity</b>	18 gal (68 l)

<b>Hydraulic System Fluid Capacity</b>	21 gal (79 l)
<b>Max Speed - high range</b>	11 mph (18 kph)
<b>Max Speed - low range</b>	6 mph (10 kph)
<b>Operating Voltage</b>	12 volts
<b>Operating Weight</b>	8,972 lbs (4,070 kg)

## Undercarriage

<b>Ground Contact Area</b>	2,556 cu in (41,885 cu cm)
<b>Ground Pressure</b>	3.5 psi
<b>Length of Track on Ground</b>	6 ft (2 m)
<b>Number of Track Rollers per Side</b>	16
<b>Width of Track</b>	18 in (46 cm)



Our Main Office