



Examples: 'Bobcat Skid Steers', 'Komatsu Dealers', 'Groff Tractor', 'Cat 316', 'Today's

Search

[CATEGORIES](#) → [COMPACT TRACK LOADERS](#) → [ASV SR-70](#)

# ASV SR-70 Compact Track Loader

**CATEGORY:** [COMPACT TRACK LOADERS](#) →

**MANUFACTURER:** [ASV](#) →

**MODEL:** [SR-70](#) →

[See all ASV SR-70s for sale](#)

## General Specifications

---

### Dimensions

---

<b>Clearance at Max Lift and Dump</b>	8 ft (2 m)
<b>Ground Clearance</b>	15 in (38 cm)
<b>Height - Top of Cab</b>	7 ft (2 m)
<b>Length - with Bucket</b>	12 ft (4 m)
<b>Length - without Bucket</b>	9 ft (3 m)
<b>Reach at Max Lift and Dump</b>	2 ft (1 m)
<b>Width Over Tracks</b>	6 ft (2 m)

## Engine

---

<b>Aspiration</b>	turbocharged
<b>Displacement</b>	201 cu in (3,300 cu cm)
<b>Engine Model</b>	804C-33T
<b>Gross Power</b>	71 hp (53 kw)
<b>Net Power</b>	68 hp (51 kw)
<b>Number of Cylinders</b>	4
<b>Peak Torque</b>	173 lbs ft (235 nm)
<b>Power Measured @</b>	2600 rpm

## Hydraulic System

---

<b>Pump Flow</b>	30 gpm (114 lpm)
<b>Relief Valve Pressure</b>	3000 psi

## Loader

---

<b>Operating Load</b>	2,750 lbs (1,247 kg)
<b>Tipping Angle</b>	5500 degrees

## Operating Specifications

---

<b>Fuel Capacity</b>	18 gal (68 l)
----------------------	---------------

<b>Hydraulic System Fluid Capacity</b>	21 gal (79 l)
<b>Operating Weight</b>	7,890 lbs (3,579 kg)

## Undercarriage

<b>Ground Contact Area</b>	2,124 cu in (34,800 cu cm)
<b>Ground Pressure</b>	3.7 psi
<b>Length of Track on Ground</b>	6 ft (2 m)
<b>Track Gauge</b>	4 ft (1 m)
<b>Width of Track</b>	15 in (38 cm)



### Our Main Office

Construction Equipment Guide  
 470 Maryland Drive  
 Fort Washington, PA 19034  
 800-523-2200

### About Us